

# 电线电缆选型样本

## Wires&Cables Catalogue



Anhui Tiangkang (Group) Shares CO.,LTD was founded in 1974, the headquarters is located in the core area of the "Yangtze River Delta" economic circle-Tianchang, after more than 40 years development, the group has gained a lot of honor, such as the top 500 enterprises of Chinese private enterprise manufacturing industry, National high-tech enterprise, State-level contract heavy-Credit Enterprises , Top 100 Enterprises of Chinese Electronic Information, Chinese quality and integrity enterprises, Bank credit AAA Enterprises, Top 100 Enterprises of Chinese electronic components, Top 10 Enterprises of Chinese wire and cable, key enterprises in Anhui Province, and the National May 1 Labor Award. Tiangkang group optical cable production plant area is nearly 200 thousand square meters, has a high crosslinking production line, mineral insulated cable production line, rubber sheathed cable production line, heating cable production line, electron irradiation accelerator production line, power cable production line and special cable production line 200 sets. The products include power cable, control cable, computer cable, new energy electric cable, silicone rubber cable, fluorine plastic cable and the data cable for communication, nuclear power cable, marine cable, locomotive cable, photovoltaic cable, wind power cable, special cable and other products, with good quality and service, are widely used in petroleum, chemical, electric power, transportation, communications, health, new energy vehicles, energy storage and other industries and fields .

As one of the backbone enterprises of the East Anhui economy with the most vitality and contribution, " striving for excellence, create satisfaction" as the goal of group, relying on first-class products, first-class management and first-class service, it not only won extensive praise in the domestic market; in international market, the products are exported to Europe, Africa, Asia and other 46 countries and regions.

Tiangkang group has gradually formed the brand culture and global business layout unique during the development, to create "high-tech, high-quality, international" brand image. Always adhering to the "leap to excellence"spirit ,on the basis of creating a harmonious enterprise, introduce the international advanced framework and model, improve the enterprise's production and management system, the organization of enterprises. On the basis of actively participating in international competition, we constantly grasp the pulse of the market development, seek the economic strategic alliance, and joint development and progress with global partners.

竭诚为客户提供一流的产品和至上的服务

Wholeheartedly Provide Customers With First-class Products and Service

## 控制电缆 Control cable



交联聚乙烯绝缘聚氯乙烯护套控制电缆

Control Cable with XLPE Insulation and PVC Sheath

聚氯乙烯绝缘及护套控制电缆

PVC Insulation & Sheath Control Cable

硅橡胶（阻燃）控制电缆

Silicon Rubber (flame retardant) Control Cable

低烟低卤阻燃控制电缆

Low Smoke Low Halogen Flame Retardant Control Cable

氟塑料绝缘耐高温控制电缆

High Temperature Resistant Control Cable with Fluoroplastic Insulation

# 聚氯乙烯绝缘和护套控制电缆

## Control Cable with PVC Insulation and Sheath

本产品适用于交流额定电压450/750V及以下控制，监控回路及保护线路等场合使用。

This product is suitable for Protective link or control & monitoring circuits, with the AC rated voltages up to and including 450/750V

### 一、生产执行标准

GB/T9330.2-2008.

### Executive standard

GB/T9330.2-2008.

### 二、使用特性

- 1、电缆导体的长期允许工作温度为70℃；
- 2、电缆的敷设温度应不低于0℃，推荐的允许弯曲半径：无铠装层的电缆，应不小于电缆外径的6倍；有铠装或铜带屏蔽结构的电缆；应不小于电缆外径的12倍；有屏蔽层结构的软电缆，应不小于电缆外径的6倍。

### Operational performance

- 1.Long term working temperature of conductor allowed by cable is 70℃.
- 2.Environment temperature for installation is no less than 0℃. Recommended Bending Radius for laying:  
For armored cable or copper tape shielding cable , not less than 12 times of cable outer diameter.For screened flexible cable and without armor cable , not less than 6 times.

### 三、电缆型号及主要使用范围

### Type , Description and Application Occasion

型号 Type	名称 Description	主要使用范围 Application occasion
KVV	铜芯聚氯乙烯绝缘聚氯乙烯护套控制电缆 Control cable with Cu core, PVC insulation and sheath	敷设在室内、电缆沟、管道固定场合 Lay in a fixed place,such as indoors, cable trench and conduit
KVVP	铜芯聚氯乙烯绝缘聚氯乙烯护套编织屏蔽控制电缆 Control cable with Cu core, PVC insulation and sheath, braided shielding	敷设在室内、电缆沟、管道等要求屏蔽的固定场合 For laying indoors, in cable trench and conduit.the cable should be shielded and for fixed installation.
KVVP2	铜芯聚氯乙烯绝缘聚氯乙烯护套铜带屏蔽控制电缆 Control cable with Cu core, PVC insulation and sheath, copper tape shielding	敷设在室内、电缆沟、管道等要求屏蔽的固定场合 For laying indoors, in cable trench and conduit.the cable should be shielded and for fixed installation.
KVVP3	铜芯聚氯乙烯绝缘聚氯乙烯护套铝塑复合带屏蔽控制电缆 Control cable with Cu conductor, PVC insulation, PVC sheath and Aluminum polyester tape	敷设在室内、电缆沟、管道等要求屏蔽的固定场合 For laying indoors, in cable trench and conduit.the cable should be shielded and for fixed installation.
KVV22	铜芯聚氯乙烯绝缘聚氯乙烯护套钢带铠装控制电缆 Control cable with Cu core, PVC insulation and sheath, steel tape armoring	敷设在室内、电缆沟、管道直埋等能承受较大机械外力的固定场合 For laying indoors, in cable trench, in conduit and underground , able to bear heavier pulling force, and for fixed installation.
KVVP2-22	铜芯聚氯乙烯绝缘聚氯乙烯护套铜带屏蔽钢带铠装控制电缆 Control cable with Cu conductor, PVC insulation, PVC sheath and steel tape armred	敷设在室内、电缆沟、管道直埋等要求屏蔽并能承受较大机械外力的固定场合 For laying indoors, in cable trench, in conduit and underground , able to bear heavier pulling force, the cable should be shielded and for fixed installation.
KVV32	铜芯聚氯乙烯绝缘聚氯乙烯护套细钢丝铠装控制电缆 Control cable with Cu core, PVC insulation and sheath, steel wire armoring	敷设在室内、电缆沟、管道竖井等能承受较大机械拉力等固定场合 For laying indoors, in trenches, in ducts and down well , able to bear heavier pulling force, and for fixed installation.
KVVR	铜芯聚氯乙烯绝缘聚氯乙烯护套控制软电缆 Control soft cable with Cu core, PVC insulation and sheath	敷设在室内移动要求柔软等场合 To be laid indoor with demand on mobility and softness
KVVRP	铜芯聚氯乙烯绝缘聚氯乙烯护套编织屏蔽控制软电缆 Control soft cable with Cu core, PVC insulation and sheath, braiding shielding	敷设在室内移动要求柔软、屏蔽等场合 To be laid indoor with demand on shielding and softness

注：①用户需要阻燃型产品，上述型号均可生产供货，只要在型号前加“Z A-、ZB-、ZC-”，如：ZA-KVV型等；

②根据用户需要，还可提供生产未列出的型号的产品，如：KVVP32、KVVP2-32等。

Note: Prefix ZA-、ZB-、ZC is added to the original type for indication of flame resistance cable, for example, ZA-KYJV.

We also produce unlisted type of cables as required, such as KVVP32、KVVP2-32 and so on.

## 各型号规格范围

## Various Specification Range

型号 Type	额定电压 V Rated voltage	导体标称截面 mm <sup>2</sup> Nominal cross section of conductor area							
		0.5	0.75	1.0	1.5	2.5	4	6	10
		芯数 Core number							
KVV KVVP	450/750	-	2~61			2~14		2~10	
KVVP2 KVVP3		-	4~61			4~14		4~10	
KVV22		-	7~61	4~61		4~14		4~10	
KVVP2-22		-	7~61	4~61		4~14		4~10	
KVV32		-	19~61	7~61		4~14		4~10	
KVVR		4~61			-	-	-		
KVVRP		4~61		4~68		-	-	-	

注：推荐的芯数系列为：2、3、4、5、7、8、10、12、14、16、19、24、27、30、37、44、48、52和61芯。

Note: Cores recommended: 2,3,4,5,7,8,10,12,14,16,19,24,27,30,37,44,48,52 or 61.

## 六、典型电缆结构及外形尺寸

## External Dimension of Common Type

## KVV型铜芯聚氯乙烯绝缘及护套控制电缆

## KVV type control cable with Cu core, PVC insulation and sheath.

芯数×标称截面 mm <sup>2</sup> Core No.*nominal cross section area	导体种类 Conductor category	外径mm Outer diameter	70°C最小绝缘电阻 mΩ.km Min insulated resistance at 70°C	芯数×标称截面 mm <sup>2</sup> Core No.*nominal cross section area	导体种类 Conductor category	外径mm Outer diameter	70°C最小绝缘电阻 mΩ.km Min insulated resistance at 70°C
2×0.75	1	7.7	0.012	3×0.75	1	8.1	0.012
2×0.75	2	7.9	0.014	3×0.75	2	8.3	0.014
2×1.0	1	8.0	0.011	3×1.0	1	8.4	0.011
2×1.0	2	8.2	0.013	3×1.0	2	8.6	0.013
2×1.5	1	8.9	0.011	3×1.5	1	9.3	0.011
2×1.5	2	9.1	0.010	3×1.5	2	9.5	0.010
2×2.5	1	10.0	0.010	3×2.5	1	10.5	0.010
2×2.5	2	10.2	0.009	3×2.5	2	10.7	0.009
2×4	1	10.9	0.0085	3×4	1	11.5	0.0085
2×4	2	11.2	0.0077	3×4	2	11.8	0.0077
2×6	1	11.8	0.0070	3×6	1	12.5	0.0070
2×6	2	12.2	0.0065	3×6	2	12.9	0.0065
2×10	2	15.3	0.0065	3×10	2	16.2	0.0065
4×0.75	1	8.6	0.012	5×0.75	1	9.2	0.012
4×0.75	2	8.8	0.014	5×0.75	2	9.4	0.014
4×1.0	1	8.9	0.011	5×1.0	1	9.6	0.011
4×1.0	2	9.2	0.013	5×1.0	2	9.8	0.013
4×1.5	1	10.0	0.011	5×1.5	1	10.7	0.011
4×1.5	2	10.2	0.010	5×1.5	2	11.0	0.010
4×2.5	1	11.4	0.010	5×2.5	1	12.3	0.010
4×2.5	2	11.6	0.009	5×2.5	2	12.5	0.009
4×4	1	12.4	0.0085	5×4	1	14.0	0.0085
4×4	2	12.8	0.0077	5×4	2	14.4	0.0077
4×6	1	14.2	0.0070	5×6	1	15.3	0.0070
4×6	2	14.6	0.0065	5×6	2	15.8	0.0065
4×10	2	17.6	0.0065	5×10	2	19.2	0.0065
7×0.75	1	9.8	0.012	8×0.75	1	10.7	0.012
7×0.75	2	10.1	0.014	8×0.75	2	11.0	0.014
7×1.0	1	10.2	0.011	8×1.0	1	11.2	0.011
7×1.0	2	10.5	0.013	8×1.0	2	11.5	0.013
7×1.5	1	11.5	0.011	8×1.5	1	12.7	0.011
7×1.5	2	11.8	0.010	8×1.5	2	13.6	0.010
7×2.5	1	13.8	0.010	8×2.5	1	15.3	0.010
7×2.5	2	14.1	0.009	8×2.5	2	15.6	0.009
7×4	1	15.1	0.0085	8×4	1	16.8	0.0085
7×4	2	15.5	0.0077	8×4	2	17.3	0.0077
7×6	1	16.6	0.0070	8×6	1	18.4	0.0070
7×6	2	17.1	0.0065	8×6	2	19.1	0.0065
7×10	2	21.3	0.0065	8×10	2	23.8	0.0065

芯数×标称截面 mm <sup>2</sup> Core No.*nominal cross section area	导体种类 Conductor category	外径mm Outer diameter	70℃最小绝缘电阻 mΩ.km Min insulated resistance at 70℃	芯数×标称截面 mm <sup>2</sup> Core No.*nominal cross section area	导体种类 Conductor category	外径mm Outer diameter	70℃最小绝缘电阻 mΩ.km Min insulated resistance at 70℃
10×0.75	1	11.8	0.012	12×0.75	1	12.2	0.012
10×0.75	2	12.2	0.014	12×0.75	2	12.6	0.014
10×1.0	1	12.4	0.011	12×1.0	1	12.8	0.011
10×1.0	2	12.8	0.013	12×1.0	2	13.8	0.013
10×1.5	1	14.7	0.011	12×1.5	1	15.2	0.011
10×1.5	2	15.1	0.010	12×1.5	2	15.5	0.010
10×2.5	1	17.0	0.010	12×2.5	1	17.5	0.010
10×2.5	2	17.4	0.009	12×2.5	2	17.9	0.009
10×4	1	18.8	0.0085	12×4	1	19.7	0.0085
10×4	2	19.7	0.0077	12×4	2	20.3	0.0077
10×6	1	21.1	0.0070	12×6	1	21.7	0.0070
10×6	2	21.8	0.0065	12×6	2	22.5	0.0065
10×10	2	26.8	0.0065	/	/	/	/
14×0.75	1	12.7	0.012	16×0.75	1	13.9	0.012
14×0.75	2	13.7	0.014	16×0.75	2	14.3	0.014
14×1.0	1	13.9	0.011	16×1.0	1	14.5	0.011
14×1.0	2	14.3	0.013	16×1.0	2	15.0	0.013
14×1.5	1	15.8	0.011	16×1.5	1	16.6	0.011
14×1.5	2	16.2	0.010	16×1.5	2	17.0	0.010
14×2.5	1	18.4	0.010	16×2.5	1	19.3	0.010
14×2.5	2	18.8	0.009	16×2.5	2	20.1	0.009
14×4	1	20.6	0.0085	24×0.75	1	16.6	0.012
14×4	2	21.3	0.0077	24×0.75	2	17.1	0.014
14×6	1	22.8	0.0070	24×1.0	1	17.4	0.011
14×6	2	23.6	0.0065	24×1.0	2	18.0	0.013
19×0.75	1	14.5	0.012	24×1.5	1	20.4	0.011
19×0.75	2	15.0	0.014	24×1.5	2	21.0	0.010
19×1.0	1	15.2	0.011	24×2.5	1	23.8	0.010
19×1.0	2	15.7	0.013	24×2.5	2	24.4	0.009
19×1.5	1	17.4	0.011	30×0.75	1	17.4	0.012
19×1.5	2	17.8	0.010	30×0.75	2	18.0	0.014
19×2.5	1	20.6	0.010	30×1.0	1	18.5	0.011
19×2.5	2	21.1	0.009	30×1.0	2	19.5	0.013
27×0.75	1	16.9	0.012	30×1.5	1	21.5	0.011
27×0.75	2	17.5	0.014	30×1.5	2	22.5	0.010
27×1.0	1	17.7	0.011	30×2.5	1	24.9	0.010
27×1.0	2	18.3	0.013	30×2.5	2	26.3	0.009
27×1.5	1	20.8	0.011	44×0.75	1	21.1	0.012
27×1.5	2	21.4	0.010	44×0.75	2	21.8	0.014
27×2.5	1	24.3	0.010	44×1.0	1	22.2	0.011
27×2.5	2	24.9	0.009	44×1.0	2	23.0	0.013
37×0.75	1	18.5	0.012	44×1.5	1	25.7	0.011
37×0.75	2	19.8	0.014	44×1.5	2	26.4	0.010
37×1.0	1	20.0	0.011	44×2.5	1	30.9	0.010
37×1.0	2	20.7	0.013	44×2.5	2	31.6	0.009
37×1.5	1	23.0	0.011	52×0.75	1	21.9	0.012
37×1.5	2	23.7	0.010	52×0.75	2	22.7	0.014
37×2.5	1	27.1	0.010	52×1.0	1	23.1	0.011
37×2.5	2	27.7	0.009	52×1.0	2	23.9	0.013
48×0.75	1	21.4	0.012	52×1.5	1	26.8	0.011
48×0.75	2	22.2	0.014	52×1.5	2	27.6	0.010
48×1.0	1	22.5	0.011	52×2.5	1	32.2	0.010
48×1.0	2	23.3	0.013	52×2.5	2	33.0	0.009
48×1.5	1	26.1	0.011	61×0.75	1	22.9	0.012
48×1.5	2	26.9	0.010	61×0.75	2	23.8	0.014
48×2.5	1	31.3	0.010	61×1.0	1	24.2	0.011
48×2.5	2	32.1	0.009	61×1.0	2	25.1	0.013
61×1.5	1	28.0	0.011	61×2.5	1	34.1	0.010
61×1.5	2	29.5	0.010	61×2.5	2	35.0	0.009

**KVVP型铜芯聚氯乙烯绝缘及护套编织屏蔽控制电缆**

**KVVP type control cable with Cu core, PVC insulation and sheath, braided shield.**

芯数×标称截面 mm <sup>2</sup> Core No.*nominal cross section area	导体种类 Conductor category	外径mm Outer diameter	70℃最小绝缘电阻 mΩ.km Min insulated resistance at 70℃	芯数×标称截面 mm <sup>2</sup> Core No.*nominal cross section area	导体种类 Conductor category	外径mm Outer diameter	70℃最小绝缘电阻 mΩ.km Min insulated resistance at 70℃
2×0.75	1	8.7	0.012	2×0.75	2	8.9	0.014
2×1.0	1	9.0	0.011	2×1.0	2	9.2	0.013
2×1.5	1	9.9	0.011	2×1.5	2	10.1	0.010
2×2.5	1	11.0	0.010	2×2.5	2	11.2	0.009
2×4	1	11.9	0.0085	2×4	2	12.2	0.0077
2×6	1	12.9	0.0070	2×6	2	13.8	0.0065
/	/	/	/	2×10	2	16.6	0.0065
3×0.75	1	9.1	0.012	3×0.75	2	9.3	0.014
3×1.0	1	9.4	0.011	3×1.0	2	9.6	0.013
3×1.5	1	10.3	0.011	3×1.5	2	10.5	0.010
3×2.5	1	11.5	0.010	3×2.5	2	11.8	0.009
3×4	1	12.5	0.0085	3×4	2	12.8	0.0077
3×6	1	14.1	0.0070	3×6	2	14.7	0.0065
/	/	/	/	3×10	2	17.4	0.0065
4×0.75	1	9.6	0.012	4×0.75	2	9.8	0.014
4×1.0	1	9.9	0.011	4×1.0	2	10.2	0.013
4×1.5	1	11.0	0.011	4×1.5	2	11.2	0.010
4×2.5	1	12.4	0.010	4×2.5	2	12.6	0.009
4×4	1	14.0	0.0085	4×4	2	14.6	0.0077
4×6	1	15.4	0.0070	4×6	2	15.9	0.0065
/	/	/	/	4×10	2	18.9	0.0065
5×0.75	1	10.2	0.012	5×0.75	2	10.4	0.014
5×1.0	1	10.6	0.011	5×1.0	2	10.8	0.013
5×1.5	1	11.7	0.011	5×1.5	2	12.0	0.010
5×2.5	1	13.9	0.010	5×2.5	2	14.1	0.009
5×4	1	15.3	0.0085	5×4	2	15.7	0.0077
5×6	1	16.6	0.0070	5×6	2	17.1	0.0065
/	/	/	/	5×10	2	20.8	0.0065
7×0.75	1	10.8	0.012	7×0.75	2	11.1	0.014
7×1.0	1	11.2	0.011	7×1.0	2	11.5	0.013
7×1.5	1	12.5	0.011	7×1.5	2	12.8	0.010
7×2.5	1	15.1	0.010	7×2.5	2	15.4	0.009
7×4	1	16.4	0.0085	7×4	2	16.8	0.0077
7×6	1	17.8	0.0070	7×6	2	18.4	0.0065
/	/	/	/	7×10	2	22.5	0.0065
8×0.75	1	11.7	0.012	8×0.75	2	12.1	0.014
8×1.0	1	12.2	0.011	8×1.0	2	12.5	0.013
8×1.5	1	14.5	0.011	8×1.5	2	14.9	0.010
8×2.5	1	16.5	0.010	8×2.5	2	16.8	0.009
8×4	1	18.0	0.0085	8×4	2	18.5	0.0077
8×6	1	20.0	0.0070	8×6	2	20.7	0.0065
/	/	/	/	8×10	2	25.2	0.0065
10×0.75	1	12.9	0.012	10×0.75	2	13.8	0.014
10×1.0	1	14.0	0.011	10×1.0	2	14.6	0.013
10×1.5	1	16.0	0.011	10×1.5	2	16.4	0.010
10×2.5	1	18.3	0.010	10×2.5	2	18.7	0.009
10×4	1	20.4	0.0085	10×4	2	21.0	0.0077
10×6	1	22.3	0.0070	10×6	2	23.1	0.0065
/	/	/	/	10×10	2	28.9	0.0065
12×0.75	1	13.8	0.012	12×0.75	2	14.2	0.014
12×1.0	1	14.6	0.011	12×1.0	2	15.0	0.013
12×1.5	1	16.4	0.011	12×1.5	2	16.8	0.010
12×2.5	1	18.8	0.010	12×2.5	2	19.2	0.009
12×4	1	21.0	0.0085	12×4	2	21.6	0.0077
12×6	1	23.0	0.0070	12×6	2	23.8	0.0065
14×0.75	1	14.5	0.012	14×0.75	2	14.9	0.014
14×1.0	1	15.2	0.011	14×1.0	2	15.6	0.013
14×1.5	1	17.1	0.011	14×1.5	2	17.5	0.010
14×2.5	1	20.0	0.010	14×2.5	2	20.4	0.009
14×4	1	21.9	0.0085	14×4	2	22.5	0.0077
14×6	1	24.0	0.0070	14×6	2	25.1	0.0065
16×0.75	1	15.1	0.012	16×0.75	2	15.6	0.014
16×1.0	1	15.8	0.011	16×1.0	2	16.2	0.013
16×1.5	1	17.8	0.011	16×1.5	2	18.3	0.010
16×2.5	1	20.9	0.010	16×2.5	2	21.4	0.009
19×0.75	1	15.7	0.012	19×0.75	2	16.2	0.014

19×1.0	1	16.5	0.011	19×1.0	2	16.9	0.013
19×1.5	1	18.6	0.011	19×1.5	2	19.1	0.010
19×2.5	1	21.9	0.010	19×2.5	2	22.4	0.009
24×0.75	1	17.8	0.012	24×0.75	2	18.4	0.014
24×1.0	1	18.7	0.011	24×1.0	2	19.2	0.013
24×1.5	1	21.6	0.011	24×1.5	2	22.2	0.010
24×2.5	1	25.3	0.010	24×2.5	2	25.9	0.009
27×0.75	1	18.1	0.012	27×0.75	2	18.7	0.014
27×1.0	1	19.0	0.011	27×1.0	2	20.0	0.013
27×1.5	1	22.0	0.011	27×1.5	2	22.6	0.010
27×2.5	1	25.8	0.010	27×2.5	2	26.4	0.009
30×0.75	1	18.6	0.012	30×0.75	2	19.3	0.014
30×1.0	1	20.0	0.011	30×1.0	2	20.6	0.013
30×1.5	1	22.7	0.011	30×1.5	2	23.3	0.010
30×2.5	1	26.7	0.010	30×2.5	2	27.3	0.009
37×0.75	1	20.2	0.012	37×0.75	2	20.9	0.014
37×1.0	1	21.3	0.011	37×1.0	2	21.9	0.013
37×1.5	1	24.3	0.011	37×1.5	2	25.2	0.010
37×2.5	1	29.1	0.010	37×2.5	2	29.8	0.009
44×0.75	1	22.3	0.012	44×0.75	2	23.1	0.014
44×1.0	1	23.5	0.011	44×1.0	2	24.2	0.013
44×1.5	1	26.8	0.011	44×1.5	2	27.9	0.010
44×2.5	1	32.0	0.010	44×2.5	2	33.3	0.009
48×0.75	1	22.2	0.012	48×0.75	2	23.4	0.014
48×1.0	1	23.5	0.011	48×1.0	2	24.6	0.013
48×1.5	1	27.1	0.011	48×1.5	2	28.9	0.010
48×2.5	1	32.5	0.010	48×2.5	2	33.6	0.009
52×0.75	1	22.6	0.012	52×0.75	2	23.7	0.014
52×1.0	1	24.3	0.011	52×1.0	2	25.4	0.013
52×1.5	1	27.9	0.011	52×1.5	2	29.6	0.010
52×2.5	1	33.4	0.010	52×2.5	2	35.0	0.009
61×0.75	1	24.0	0.012	61×0.75	2	24.9	0.014
61×1.0	1	25.5	0.011	61×1.0	2	26.5	0.013
61×1.5	1	29.9	0.011	61×1.5	2	30.9	0.010
61×2.5	1	35.7	0.010	61×2.5	2	37.1	0.009



**KVVP2(P3)型铜芯聚氯乙烯绝缘及护套铜带(铝塑复合带)屏蔽控制电缆**

**Control cable with Cu core, PVC insulation, PVC sheath and Copper tape /Aluminum polyester tape shielding (KVVP2/P3).**

芯数×标称截面 mm <sup>2</sup> Core No.*nominal cross section area	导体种类 Conductor category	外径mm Outer diameter	70°C最小绝缘电阻 mΩ.km Min insulated resistance at 70°C	芯数×标称截面 mm <sup>2</sup> Core No.*nominal cross section area	导体种类 Conductor category	外径mm Outer diameter	70°C最小绝缘电阻 mΩ.km Min insulated resistance at 70°C
4×0.75	1	9.1	0.012	5×0.75	1	9.6	0.012
4×1.0	1	9.4	0.011	5×1.0	1	10.0	0.011
4×1.5	1	10.5	0.011	5×1.5	1	11.2	0.011
4×2.5	1	11.9	0.010	5×2.5	1	12.8	0.010
4×4	1	13.5	0.0085	5×4	1	14.5	0.0085
4×6	1	14.6	0.0070	5×6	1	15.8	0.0070
4×10	2	18.1	0.0065	5×10	2	20.1	0.0065
7×0.75	1	10.3	0.012	8×0.75	1	11.2	0.012
7×1.0	1	10.7	0.011	8×1.0	1	11.7	0.011
7×1.5	1	12.0	0.011	8×1.5	1	13.8	0.011
7×2.5	1	14.3	0.010	8×2.5	1	15.7	0.010
7×4	1	15.6	0.0085	8×4	1	17.2	0.0085
7×6	1	17.0	0.0070	8×6	1	18.9	0.0070
7×10	2	21.7	0.0065	8×10	2	24.2	0.0065
10×0.75	1	12.3	0.012	10×4	1	19.6	0.0085
10×1.0	1	13.5	0.011	10×6	1	21.5	0.0070
10×1.5	1	15.2	0.011	10×10	2	27.3	0.0065
10×2.5	1	17.5	0.010	/	/	/	/
12×0.75	1	12.7	0.012	14×0.75	1	13.2	0.012
12×1.0	1	13.8	0.011	14×1.0	1	14.4	0.011
12×1.5	1	15.6	0.011	14×1.5	1	16.3	0.011
12×2.5	1	18.0	0.010	14×2.5	1	18.8	0.010
12×4	1	20.2	0.0085	14×4	1	21.1	0.0085
12×6	1	22.2	0.0070	14×6	1	23.2	0.0070
16×0.75	1	14.3	0.012	19×0.75	1	15.0	0.012
16×1.0	1	15.0	0.011	19×1.0	1	15.7	0.011
16×1.5	1	17.1	0.011	19×1.5	1	17.8	0.011
16×2.5	1	20.1	0.010	19×2.5	1	21.1	0.010
24×0.75	1	17.0	0.012	27×0.75	1	17.3	0.012
24×1.0	1	17.9	0.011	27×1.0	1	18.2	0.011
24×1.5	1	20.9	0.011	27×1.5	1	21.3	0.011
24×2.5	1	24.3	0.010	27×2.5	1	24.8	0.010
30×0.75	1	17.9	0.012	37×0.75	1	19.1	0.012
30×1.0	1	18.8	0.011	37×1.0	1	20.5	0.011
30×1.5	1	22.0	0.011	37×1.5	1	23.5	0.011
30×2.5	1	25.6	0.010	37×2.5	1	27.5	0.010
44×0.75	1	21.5	0.012	48×0.75	1	21.9	0.012
44×1.0	1	22.7	0.011	48×1.0	1	23.0	0.011
44×1.5	1	26.2	0.011	48×1.5	1	26.5	0.011
44×2.5	1	31.3	0.010	48×2.5	1	31.8	0.010
52×0.75	1	22.4	0.012	61×0.75	1	23.6	0.012
52×1.0	1	23.6	0.011	61×1.0	1	24.9	0.011
52×1.5	1	27.2	0.011	61×1.5	1	29.4	0.011
52×2.5	1	32.7	0.010	61×2.5	1	34.9	0.010

**KVV22型铜芯聚氯乙烯绝缘及护套钢带铠装控制电缆**

**KVV22 type control cable with Cu core, PVC insulation and sheath, steel tape armoring.**

芯数×标称截面 mm <sup>2</sup> Core No.*nominal cross section area	导体种类 Conductor category	外径mm Outer diameter	70°C最小绝缘电阻 mΩ.km Min insulated resistance at 70°C	芯数×标称截面 mm <sup>2</sup> Core No.*nominal cross section area	导体种类 Conductor category	外径mm Outer diameter	70°C最小绝缘电阻 mΩ.km Min insulated resistance at 70°C
4×1.5	1	13.0	0.011	5×1.5	1	13.7	0.011
4×2.5	1	14.4	0.010	5×2.5	1	15.3	0.010
4×4	1	15.4	0.0085	5×4	1	16.4	0.0085
4×6	1	16.6	0.0070	5×6	1	17.7	0.0070
4×10	2	20.4	0.0065	5×10	2	22.0	0.0065
7×0.75	1	12.8	0.012	8×0.75	1	13.7	0.012
7×1.0	1	13.2	0.011	8×1.0	1	14.2	0.011
7×1.5	1	14.5	0.011	8×1.5	1	15.7	0.011
7×2.5	1	16.2	0.010	8×2.5	1	17.7	0.010
7×4	1	17.5	0.0085	8×4	1	19.2	0.0085
7×6	1	19.0	0.0070	8×6	1	21.2	0.0070
7×10	2	23.7	0.0065	8×10	2	26.2	0.0065
10×0.75	1	14.8	0.012	14×0.75	1	15.7	0.012
10×1.0	1	15.4	0.011	14×1.0	1	16.3	0.011
10×1.5	1	17.1	0.011	14×1.5	1	18.2	0.011
10×2.5	1	19.8	0.010	14×2.5	1	21.1	0.010
10×4	1	21.5	0.0085	14×4	1	23.0	0.0085
10×6	1	23.5	0.0070	14×6	1	25.2	0.0070
10×10	2	30.2	0.0065	16×0.75	1	16.3	0.012
12×0.75	1	15.1	0.012	16×1.0	1	17.0	0.011
12×1.0	1	15.8	0.011	16×1.5	1	19.0	0.011
12×1.5	1	17.6	0.011	16×2.5	1	22.1	0.010
12×2.5	1	20.3	0.010	19×0.75	1	16.9	0.012
12×4	1	22.1	0.0085	19×1.0	1	17.6	0.011
12×6	1	24.1	0.0070	19×1.5	1	20.2	0.011
/	/	/	/	19×2.5	1	23.0	0.010
24×0.75	1	19.0	0.012	27×0.75	1	19.7	0.012
24×1.0	1	20.2	0.011	27×1.0	1	20.5	0.011
24×1.5	1	22.8	0.011	27×1.5	1	23.2	0.011
24×2.5	1	26.6	0.010	27×2.5	1	27.1	0.010
30×0.75	1	20.2	0.012	37×0.75	1	21.4	0.012
30×1.0	1	21.1	0.011	37×1.0	1	22.4	0.011
30×1.5	1	23.9	0.011	37×1.5	1	25.4	0.011
30×2.5	1	28.0	0.010	37×2.5	1	30.4	0.010
44×0.75	1	23.5	0.012	48×0.75	1	23.8	0.012
44×1.0	1	24.6	0.011	48×1.0	1	25.0	0.011
44×1.5	1	29.0	0.011	48×1.5	1	29.4	0.011
44×2.5	1	34.0	0.010	48×2.5	1	34.5	0.010
52×0.75	1	24.3	0.012	61×0.75	1	25.5	0.012
52×1.0	1	25.5	0.011	61×1.0	1	27.2	0.011
52×1.5	1	30.1	0.011	61×1.5	1	31.7	0.011
52×2.5	1	36.5	0.010	61×2.5	1	38.4	0.010

**KVVP2-22型铜芯聚氯乙烯绝缘及护套铜带屏蔽钢带铠装控制电缆**

**Control cable with Cu core, PVC insulation & sheath, Copper tape shielding and steel tape armored (KVVP2-22).**

芯数×标称截面 mm <sup>2</sup> Core No.*nominal cross section area	导体种类 Conductor category	外径mm Outer diameter	70°C最小绝缘电阻 mΩ.km Min insulated resistance at 70°C	芯数×标称截面 mm <sup>2</sup> Core No.*nominal cross section area	导体种类 Conductor category	外径mm Outer diameter	70°C最小绝缘电阻 mΩ.km Min insulated resistance at 70°C
4×1.5	1	13.7	0.011	5×1.5	1	14.5	0.011
4×2.5	1	15.1	0.010	5×2.5	1	16.0	0.010
4×4	1	16.2	0.0085	5×4	1	17.2	0.0085
4×6	1	17.3	0.0070	5×6	1	18.5	0.0070
4×10	2	21.2	0.0065	5×10	2	22.8	0.0065
7×0.75	1	13.5	0.012	8×0.75	1	14.5	0.012
7×1.0	1	14.0	0.011	8×1.0	1	15.0	0.011
7×1.5	1	15.3	0.011	8×1.5	1	16.4	0.011
7×2.5	1	17.0	0.010	8×2.5	1	18.4	0.010
7×4	1	18.3	0.0085	8×4	1	20.3	0.0085
7×6	1	20.1	0.0070	8×6	1	22.0	0.0070
7×10	2	24.4	0.0065	8×10	2	27.3	0.0065
10×0.75	1	15.6	0.012	10×4	1	22.3	0.0085
10×1.0	1	16.2	0.011	10×6	1	24.2	0.0070
10×1.5	1	17.9	0.011	10×10	2	31.0	0.0065
10×2.5	1	20.6	0.010	/	/	/	/
12×0.75	1	15.9	0.012	14×0.75	1	16.4	0.012
12×1.0	1	16.5	0.011	14×1.0	1	17.1	0.011
12×1.5	1	18.3	0.011	14×1.5	1	19.4	0.011
12×2.5	1	21.1	0.010	14×2.5	1	21.9	0.010
12×4	1	22.9	0.0085	14×4	1	23.8	0.0085
12×6	1	24.9	0.0070	14×6	1	25.9	0.0070
16×0.75	1	17.0	0.012	19×0.75	1	17.7	0.012
16×1.0	1	17.7	0.011	19×1.0	1	18.4	0.011
16×1.5	1	20.1	0.011	19×1.5	1	20.9	0.011
16×2.5	1	22.8	0.010	19×2.5	1	23.8	0.010
24×0.75	1	20.1	0.012	27×0.75	1	20.4	0.012
24×1.0	1	21.0	0.011	27×1.0	1	21.3	0.011
24×1.5	1	23.6	0.011	27×1.5	1	24.0	0.011
24×2.5	1	27.4	0.010	27×2.5	1	27.9	0.010
30×0.75	1	21.0	0.012	37×0.75	1	22.2	0.012
30×1.0	1	21.9	0.011	37×1.0	1	23.2	0.011
30×1.5	1	24.6	0.011	37×1.5	1	26.6	0.011
30×2.5	1	29.3	0.010	37×2.5	1	31.2	0.010
44×0.75	1	24.2	0.012	48×0.75	1	24.5	0.012
44×1.0	1	25.4	0.011	48×1.0	1	25.7	0.011
44×1.5	1	29.8	0.011	48×1.5	1	30.2	0.011
44×2.5	1	34.8	0.010	48×2.5	1	36.4	0.010
52×0.75	1	25.9	0.012	61×0.75	1	26.7	0.012
52×1.0	1	27.6	0.011	61×1.0	1	28.0	0.011
52×1.5	1	31.9	0.011	61×1.5	1	32.4	0.011
52×2.5	1	38.5	0.010	61×2.5	1	39.2	0.010

**KVV32型铜芯聚氯乙烯绝缘及护套钢丝铠装控制电缆**

**Control cable with Cu core, PVC insulation, & sheath and steel wire armored (KVV32).**

芯数×标称截面 mm <sup>2</sup> Core No.*nominal cross section area	导体种类 Conductor category	外径mm Outer diameter	70°C最小绝缘电阻 mΩ.km Min insulated resistance at 70°C	芯数×标称截面 mm <sup>2</sup> Core No.*nominal cross section area	导体种类 Conductor category	外径mm Outer diameter	70°C最小绝缘电阻 mΩ.km Min insulated resistance at 70°C
4×4	1	17.0	0.0085	5×4	1	18.0	0.0085
4×6	1	18.2	0.0070	5×6	1	19.7	0.0070
4×10	2	22.7	0.0065	5×10	2	24.3	0.0065
7×1.5	1	16.1	0.011	8×1.5	1	17.3	0.011
7×2.5	1	17.8	0.010	8×2.5	1	19.7	0.010
7×4	1	19.1	0.0085	8×4	1	21.8	0.0085
7×6	1	21.0	0.0070	8×6	1	23.5	0.0070
7×10	2	26.0	0.0065	8×10	2	28.5	0.0065
10×1.5	1	18.8	0.011	10×4	1	23.8	0.0085
10×2.5	1	22.1	0.010	10×6	1	25.8	0.0070
10×10	2	33.3	0.0065	/	/	/	/
12×1.5	1	19.2	0.011	14×1.5	1	20.2	0.011
12×2.5	1	22.6	0.010	14×2.5	1	23.4	0.010
12×4	1	24.4	0.0085	14×4	1	25.3	0.0085
12×6	1	26.4	0.0070	14×6	1	27.5	0.0070
16×1.5	1	21.0	0.011	19×0.75	1	18.5	0.012
16×2.5	1	24.4	0.010	19×1.0	1	19.2	0.011
24×0.75	1	21.0	0.012	19×1.5	1	22.5	0.011
24×1.0	1	22.5	0.011	19×2.5	1	25.3	0.010
24×1.5	1	25.1	0.011	27×0.75	1	21.9	0.012
24×2.5	1	29.5	0.010	27×1.0	1	22.8	0.011
30×0.75	1	22.5	0.012	27×1.5	1	25.5	0.011
30×1.0	1	23.4	0.011	27×2.5	1	30.0	0.010
30×1.5	1	26.2	0.011	37×0.75	1	23.7	0.012
30×2.5	1	30.8	0.010	37×1.0	1	24.7	0.011
44×0.75	1	25.8	0.012	37×1.5	1	27.7	0.011
44×1.0	1	26.9	0.011	37×2.5	1	33.5	0.010
44×1.5	1	31.3	0.011	48×0.75	1	26.1	0.012
44×2.5	1	37.1	0.010	48×1.0	1	27.3	0.011
52×0.75	1	26.1	0.012	48×1.5	1	31.7	0.011
52×1.0	1	27.3	0.011	48×2.5	1	37.6	0.010
52×1.5	1	31.7	0.011	61×0.75	1	27.8	0.012
52×2.5	1	37.6	0.010	61×1.0	1	30.1	0.011
61×1.5	1	35.1	0.011	61×2.5	1	40.3	0.010

**KVVR型铜芯聚氯乙烯绝缘及护套控制软电缆**

**Copper core control flexible cable, PVC insulation&sheath (KVVR).**

芯数×标称截面 mm <sup>2</sup> Core No.*nominal cross section area	导体种类 Conductor category	外径mm Outer diameter	70°C最小绝缘电阻 mΩ.km Min insulated resistance at 70°C	芯数×标称截面 mm <sup>2</sup> Core No.*nominal cross section area	导体种类 Conductor category	外径mm Outer diameter	70°C最小绝缘电阻 mΩ.km Min insulated resistance at 70°C
2×0.5	5	7.4	0.013	3×0.5	5	7.8	0.013
2×0.75	5	7.7	0.011	3×0.75	5	8.1	0.011
2×1.0	5	8.0	0.010	3×1.0	5	8.4	0.010
2×1.5	5	8.9	0.010	3×1.5	5	9.3	0.010
2×2.5	5	10.1	0.009	3×2.5	5	10.7	0.009
4×0.5	5	8.3	0.013	5×0.5	5	8.9	0.013
4×0.75	5	8.6	0.011	5×0.75	5	9.3	0.011
4×1.0	5	9.0	0.010	5×1.0	5	9.6	0.010
4×1.5	5	10.0	0.010	5×1.5	5	10.8	0.010
4×2.5	5	11.5	0.009	5×2.5	5	12.5	0.009
7×0.5	5	9.5	0.013	8×0.5	5	10.4	0.013
7×0.75	5	9.9	0.011	8×0.75	5	10.9	0.011
7×1.0	5	10.3	0.010	8×1.0	5	11.4	0.010
7×1.5	5	11.6	0.010	8×1.5	5	13.5	0.010
7×2.5	5	14.1	0.009	8×2.5	5	15.6	0.009
10×0.5	5	11.5	0.013	12×0.5	5	11.9	0.013
10×0.75	5	12.1	0.011	12×0.75	5	12.5	0.011
10×1.0	5	13.3	0.010	12×1.0	5	13.7	0.010
10×1.5	5	15.0	0.010	12×1.5	5	15.4	0.010
10×2.5	5	17.5	0.009	12×2.5	5	18.0	0.009
14×0.5	5	12.4	0.013	16×0.5	5	13.6	0.013
14×0.75	5	13.6	0.011	16×0.75	5	14.2	0.011
14×1.0	5	14.2	0.010	16×1.0	5	14.9	0.010
14×1.5	5	16.1	0.010	16×1.5	5	17.0	0.010
14×2.5	5	18.9	0.009	16×2.5	5	20.3	0.009
19×0.5	5	14.2	0.013	24×0.5	5	16.3	0.013
19×0.75	5	14.9	0.011	24×0.75	5	17.1	0.011
19×1.0	5	15.6	0.010	24×1.0	5	18.0	0.010
19×1.5	5	17.8	0.010	24×1.5	5	21.0	0.010
19×2.5	5	21.3	0.009	24×2.5	5	24.7	0.009
27×0.5	5	16.6	0.013	30×0.5	5	17.1	0.013
27×0.75	5	17.4	0.011	30×0.75	5	18.0	0.011
27×1.0	5	18.3	0.010	30×1.0	5	18.9	0.010
27×1.5	5	21.4	0.010	30×1.5	5	22.1	0.010
27×2.5	5	25.2	0.009	30×2.5	5	26.1	0.009
37×0.5	5	18.3	0.013	44×0.5	5	20.8	0.013
37×0.75	5	19.7	0.011	44×0.75	5	21.9	0.011
37×1.0	5	20.7	0.010	44×1.0	5	23.1	0.010
37×1.5	5	23.7	0.010	44×1.5	5	26.5	0.010
37×2.5	5	28.7	0.009	44×2.5	5	32.1	0.009
48×0.5	5	21.1	0.013	52×0.5	5	21.6	0.013
48×0.75	5	22.2	0.011	52×0.75	5	22.8	0.011
48×1.0	5	23.4	0.010	52×1.0	5	24.0	0.010
48×1.5	5	26.9	0.010	52×1.5	5	27.7	0.010
48×2.5	5	32.6	0.009	52×2.5	5	33.9	0.009
61×0.5	5	22.8	0.013	61×1.5	5	29.9	0.010
61×0.75	5	24.1	0.011	61×2.5	5	35.9	0.009
61×1.0	5	25.4	0.010	/	/	/	/

**KVVRP型铜芯聚氯乙烯绝缘及护套编织屏蔽控制软电缆**

**Control soft cable with Cu conductor, PVC insulation&sheath and copper braided shield (KVVRP).**

芯数×标称截面 mm <sup>2</sup> Core No.*nominal cross section area	导体种类 Conductor category	外径mm Outer diameter	70°C最小绝缘电阻 mΩ.km Min insulated resistance at 70°C	芯数×标称截面 mm <sup>2</sup> Core No.*nominal cross section area	导体种类 Conductor category	外径mm Outer diameter	70°C最小绝缘电阻 mΩ.km Min insulated resistance at 70°C
2×0.5	5	8.4	0.013	3×0.5	5	8.8	0.013
2×0.75	5	8.7	0.011	3×0.75	5	9.1	0.011
2×1.0	5	9.0	0.010	3×1.0	5	9.4	0.010
2×1.5	5	9.9	0.010	3×1.5	5	10.3	0.010
2×2.5	5	11.1	0.009	3×2.5	5	11.7	0.009
4×0.5	5	9.3	0.013	5×0.5	5	9.9	0.013
4×0.75	5	9.6	0.011	5×0.75	5	10.3	0.011
4×1.0	5	10.0	0.010	5×1.0	5	10.7	0.010
4×1.5	5	11.0	0.010	5×1.5	5	11.8	0.010
4×2.5	5	12.5	0.009	5×2.5	5	14.3	0.009
7×0.5	5	10.5	0.013	8×0.5	5	11.4	0.013
7×0.75	5	10.9	0.011	8×0.75	5	11.9	0.011
7×1.0	5	11.4	0.010	8×1.0	5	12.4	0.010
7×1.5	5	13.2	0.010	8×1.5	5	14.7	0.010
7×2.5	5	15.3	0.009	8×2.5	5	16.9	0.009
10×0.5	5	12.6	0.013	12×0.5	5	13.5	0.013
10×0.75	5	13.7	0.011	12×0.75	5	14.3	0.011
10×1.0	5	14.5	0.010	12×1.0	5	14.9	0.010
10×1.5	5	16.3	0.010	12×1.5	5	16.7	0.010
10×2.5	5	18.7	0.009	12×2.5	5	19.7	0.009
14×0.5	5	14.2	0.013	16×0.5	5	14.8	0.013
14×0.75	5	14.9	0.011	16×0.75	5	15.5	0.011
14×1.0	5	15.5	0.010	16×1.0	5	16.2	0.010
14×1.5	5	17.4	0.010	16×1.5	5	18.2	0.010
14×2.5	5	20.5	0.009	16×2.5	5	21.5	0.009
19×0.5	5	15.4	0.013	24×0.5	5	17.5	0.013
19×0.75	5	16.2	0.011	24×0.75	5	18.4	0.011
19×1.0	5	16.9	0.010	24×1.0	5	19.6	0.010
19×1.5	5	19.4	0.010	24×1.5	5	22.2	0.010
19×2.5	5	22.5	0.009	24×2.5	5	26.2	0.009
27×0.5	5	17.8	0.013	30×0.5	5	18.3	0.013
27×0.75	5	18.7	0.011	30×0.75	5	19.7	0.011
27×1.0	5	20.0	0.010	30×1.0	5	20.6	0.010
27×1.5	5	22.6	0.010	30×1.5	5	23.3	0.010
27×2.5	5	26.7	0.009	30×2.5	5	27.6	0.009
37×0.5	5	19.9	0.013	44×0.5	5	22.0	0.013
37×0.75	5	21.0	0.011	44×0.75	5	23.2	0.011
37×1.0	5	22.0	0.010	44×1.0	5	24.6	0.010
37×1.5	5	25.2	0.010	44×1.5	5	28.6	0.010
37×2.5	5	30.2	0.009	44×2.5	5	34.0	0.009
48×0.5	5	22.3	0.013	52×0.5	5	22.9	0.013
48×0.75	5	23.5	0.011	52×0.75	5	24.1	0.011
48×1.0	5	24.9	0.010	52×1.0	5	25.5	0.010
48×1.5	5	29.0	0.010	61×0.5	5	24.1	0.013
48×2.5	5	34.5	0.009	61×0.75	5	25.6	0.011
/	/	/	/	61×1.0	5	26.9	0.010